

Printing date 07.03.2023 Version number 2 (replaces version 1) Revision: 10.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name Weber M100/600

Safety data sheet no.: XXP01000209

1.2 Relevant identified uses of the substance or mixture and uses advised against

The product is intended for industrial or professional use.

Application of the substance / the mixture Mortars for Construction

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Eesti AS

Peterburi tee 75

Tallinn 13816, Estonia

Phone: +372 6200 9510

eesti@saint-gobain.com

1.4 Emergency telephone number:

Estonia: 166662 - Poison Information Centre of the Public Health Agency

Latvia: 11 2 - Valsts ugunsdzēsības un glābšanas dienests (State Fire and Rescue Service); +371 67042473 - Toksikoloģijas un sepses klīnikas Saindēšanās un zāļu informācijas centrs, Hipokrāta 2, Rīga, Latvija, LV-1038 (Poisoning and Drug Information Center of the Toxicology and Sepsis Clinic) Lithuania: + 370 5 236 20 52; + 370 687 53378 (mob.) - Lietuvos apsinuodijimų kontrolės ir informacijos biuras (neatidėliotina informacija apsinuodijus) Lithuanian Poison Control and Information Office (urgent information in case of poisoning)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS05 GHS07

Signal word Danger

(Contd. on page 2)



Printing date 07.03.2023 Version number 2 (replaces version 1) Revision: 10.02.2023

Trade name Weber M100/600

(Contd. of page 1)

Hazard-determining components of labelling:

cement clinker

Oil shale, thermal processing waste

Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

2.3 Other hazards

Under the conditions of conservation, the reducing agent used keeps the content of soluble chromium (VI) below 2 ppm until the expiration date indicated.

The product contains silica sand with less than 1% of fine fraction and therefore is not classified as hazardous; however, pay attention when handling and follow the indications relating to personal protective equipment.

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances. **vPvB:** Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture consisting of the following components.

Dangerous components:		
CAS: 14808-60-7 EINECS: 238-878-4	Silicon dioxide (Quartz sand) substance with a Community workplace exposure limit	75-100%
CAS: 65997-15-1 EINECS: 266-043-4	cement clinker Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 % Eye Dam. 1; H318: C ≥ 1 %	10-20%
CAS: 1317-65-3 EINECS: 215-279-6	calcium carbonate substance with a Community workplace exposure limit	5-10%
CAS: 93685-99-5 EINECS: 297-648-1 Reg.nr.: 01-2119703178-42-xxxx	Oil shale, thermal processing waste ♦ STOT RE 2, H373; ♦ Eye Dam. 1, H318; ♦ STOT SE 3, H335	1-2%

SVHC Void

(Contd. on page 3)



Printing date 07.03.2023

Version number 2 (replaces version 1)

Trade name Weber M100/600

(Contd. of page 2)

Revision: 10.02.2023

Additional information

The mixture is "low chromate" according to the Regulation (EC) No 1272/2008 within the product shelf-life, so that the classification with H317 is not applicable, when the packing was not opened in the meantime.

The product contains silica sand composed of quartz (crystalline silica) with a fine fraction below 1%. The respirable fraction has an occupational exposure limit value (cf. section 8).

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Immediately remove any clothing soiled by the product.

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

After inhalation

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air and to be sure call for a doctor.

After skin contact Immediately wash with water and soap and rinse thoroughly.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

This powder (wet or dry) may cause irritation or potentially irreversible serious injury on contact with the eyes. Prolonged contact with moist skin (due to e.g. sweat or humidity) can cause skin irritation

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents The product is not combustible.

- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- 5.3 Advice for firefighters

Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** No special measures required.
- 6.3 Methods and material for containment and cleaning up:

The dry powder and the fresh product is removed with water. The hardened product is removed mechanically.

Ensure adequate ventilation.

(Contd. on page 4)

(Contd. of page 3)



Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 07.03.2023 Version number 2 (replaces version 1) Revision: 10.02.2023

Trade name Weber M100/600

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Thorough dedusting.

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

	·			
DNELs				
CAS: 93685-99-5 Oil shale, thermal processing waste				
Inhalative Derived No Effect Level 0.233 mg/m³ (worker local long term value)				
	0.233 mg/m³ (consumer local short term value)			
CAS No. / Designa	CAS No. / Designation of material / % / Type / Value / Unit			
CAS: 14808-60-7 Silic	con dioxide (Quartz sand)			
BOELV (European Uni	ion) Long-term value: 0.1* mg/m³ *respirable fraction			
MAK (Germany)	Long-term value: 0.05 mg/m³ alveolengängige Fraktion			
GV (Denmark)	Short-term value: 0.6* 0.2** mg/m³ Long-term value: 0.3* 0.1** mg/m³ *total:,**total, respirabel, EK			
LEP (Spain)	Long-term value: 0.05 mg/m³ *Fracción resp:n,d,y			
TWA (Italy)	Long-term value: 0.025 mg/m³ A2, (j)			
VLE (Portugal)	Long-term value: 0.05 mg/m³ Resp.;A2; fibrose pulmonar; cancro do pulmão			
	(Contd. on page 5)			

(Contd. on page 5)



Printing date 07.03.2023 Version number 2 (replaces version 1) Revision: 10.02.2023

Trade name Weber M100/600

		(Contd. of page 4)
OEL (Sweden)	Long-term value: 0.1 mg/m³ C, M, respirabel fraktion	
HTP (Finland)	Long-term value: 0.05 0.1* mg/m³ alveolijae;*sitovat raja-arvot, pöly	
CAS: 65997-15-1 cement	clinker	
AGW (Germany)	Long-term value: 5 E mg/m³ DFG	
LEP (Spain)	Long-term value: 4 mg/m³ fracción respirable: e, d	
TWA (Italy)	Long-term value: 1 mg/m³ (e, j), A4	
VLE (Portugal)	Long-term value: 1 mg/m³ Fração resp.;A4,função pulm.,sintomas resp.,asma	
HTP (Finland)	Long-term value: 5* 1** mg/m³ *hengittyvä pöly, **alveolijae	
CAS: 1317-65-3 calcium	carbonate	
TWA (Italy)	Long-term value: 10 mg/m³ (e)	

Additional Occupational Exposure Limit Values for possible hazards during processing:

Quartz respirable dust (< 5 µm): 0,15 mg/m³

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection Protective gloves.Eye/face protection Safety glasses.Body protection: Protective work clothing.

9.1 Information on basic physical and chemical properties

SECTION 9: Physical and chemical properties

General Information

Physical state Solid.

Colour: Grey
Odour: Odourless
Odour threshold: Not determined.

Melting point/freezing point: Undetermined.

(Contd. on page 6)



Printing date 07.03.2023 Version number 2 (replaces version 1) Revision: 10.02.2023

Trade name Weber M100/600

(Contd. of page 5)

Boiling point or initial boiling point and boiling

range Undetermined.

Flammability Product is not flammable.

Lower and upper explosion limit

Lower:Not determined.Upper:Not determined.Flash point:Not applicableIgnition temperature:Not determined.Decomposition temperature:Not determined.

pH at 20 °C 12-13

Alkaline

Viscosity:

Kinematic viscosity

dynamic:

Not applicable.

Not applicable.

Solubility

Water: Miscible

Partition coefficient n-octanol/water (log value) Not determined. Vapour pressure:

Not applicable.

Density and/or relative density

Density at 20 °C: 1.4-1.6 g/cm³ (DIN 51757)

Not applicable. Not determined. Not applicable.

Vapour densityNot applicateParticle characteristicsSee item 3.

9.2 Other informationNo further relevant information available.

Appearance:

Relative density

Form: Powder

Important information on protection of health

and environment, and on safety.

Auto-ignition temperature: Product is not self-igniting.

Explosive properties: Product does not present an explosion hazard.

EU-VOC (g/L)

Solids content: 100.0 %

Change in condition Softening point/range

Oxidising properties

Evaporation rate

Not determined.

Not applicable.

Information with regard to physical hazard

classes

Explosives Void Flammable gases Void **Aerosols** Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void **Pyrophoric liquids** Void Pyrophoric solids Void

(Contd. on page 7)



Printing date 07.03.2023 Version number 2 (replaces version 1) Revision: 10.02.2023

Trade name Weber M100/600

Self-heating substances and mixtures
Substances and mixtures, which emit
flammable gases in contact with water
Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals

Void
Void
Void
Void
Void

Void

SECTION 10: Stability and reactivity

10.1 Reactivity When mixed with water the product hardens forming a stable non-reactive mass.

10.2 Chemical stability Stable at recommended storage conditions

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known

10.4 Conditions to avoid

Desensitised explosives

Avoid water ingress/moisture during storage (the product will react with moisture and harden).

10.5 Incompatible materials: Acids, ammonium salts, aluminum, non-precious metals.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Compon	nents	1	Type	1	Value	1	Species	
CAS: 65	997-1	5-1 cement o	clinker					
Dermal	LD50	>2,000 mg/k	g (Rabbit)					
CAS: 13	17-65	-3 calcium c	arbonate					
Oral	LD50	>5,000 mg/k	g (Rat)					
CAS: 93	685-9	9-5 Oil shale	, thermal	proc	essing w	ast	te	
Oral	LD50	>2,000 mg/k	g (Rat)					

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/irritation Causes serious eye damage.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 8)



Printing date 07.03.2023 Version number 2 (replaces version 1) Revision: 10.02.2023

Trade name Weber M100/600

(Contd. of page 7)

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Not classified as harmful to aquatic life

Type of test	Type of test / Effective concentration / Method / Assessment		
CAS: 1317-65-3 calcium carbonate			
LC50/96h	>10,000 mg/l (Oncorhynchus mykiss (Rainbow trout))		
EC50/48h	>1,000 mg/l (Daphnia magna)		
EC50/72h	>200 mg/l (Algae)		
CAS: 93685-	CAS: 93685-99-5 Oil shale, thermal processing waste		
EC50/48h	100 mg/l (Daphnia magna)		
EC50/72h	82.7 mg/l (Algae)		
NOEC (72h)	NOEC (72h) 3.2 mg/l (Algae)		
NOEC (21d)	NOEC (21d) 1 mg/l (Daphnia magna)		

- **12.2 Persistence and degradability** The product is not biodegradable.
- 12.3 Bioaccumulative potential Does not accumulate in organisms
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

Behaviour in sewage processing plants:

Type of test / Effective concentration / Method / Assessment	
CAS: 93685-99-5 Oil shale, thermal processing waste	
EC 50 (3h) 1,000 mg/l (Activated sludge)	

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- EUG



Printing date 07.03.2023 Version number 2 (replaces version 1) Revision: 10.02.2023

Trade name Weber M100/600

(Contd. of page 8)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish. Possible waste code 17 09 04.

Europea	European waste catalogue			
10 13 11	wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10			
10 13 14	waste concrete and concrete sludge			
17 09 04	mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03			
HP4	Irritant - skin irritation and eye damage			
HP13	Sensitising			

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleaning agent:

Water, if necessary together with cleansing agents.

Thoroughly shake out sacks.

14.1 UN number or ID number ADR, IMDG, IATA	Void
14.2 UN proper shipping name ADR, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according IMO instruments	ng to Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications
UN "Model Regulation":	Void





Revision: 10.02.2023 Printing date 07.03.2023 Version number 2 (replaces version 1)

Trade name Weber M100/600

(Contd. of page 9)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

Cement clinker is exempted from REACH registration (REACH Article 2(7)(b) and Annex V point 10)

Labelling according to Regulation (EC) No 1272/2008 cf. section 2

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII point 47 Chromium VI compounds)

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However. this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation Skin sensitisation

The classification of the mixture is generally based on the calculation Serious eye damage/irritation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS: Marketing

(Contd. on page 11)





Printing date 07.03.2023 Version number 2 (replaces version 1) Revision: 10.02.2023

Trade name Weber M100/600

(Contd. of page 10)

Contact:

Priit Pallum

Phone: +372 6200 9510 eesti@saint-gobain.com

Version number of previous version: 1

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative Skin Corr. 1A: Skin corrosion/irritation - Category 1A Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

* Data compared to the previous version altered.

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.